


## With the usual collaxx advantages:




## Compatibility

There are no limits to your creativity:
You can arbitrarily combine all collaxx colour light units.



It is only a few steps to utter relaxation.

Ideal for retrofitting: Facile installation with only 2 screws.



Technical data colour light unit	FL201F	FL201VF
Recommended cabin size	up to 2.5 x 2.5 m	
Cut-out of the ceiling	no cut-out	300 x 215 mm
Dimensions	320 x 235 x 35 mm	
Weight	ca. 730 g	ca. 600 g
Light intensity	red: typ. 225 lm; orange: typ. 290 lm; yellow: typ. 225 lm; green: typ. 150 lm; turquoise: typ. 165 lm; blue: typ. 45 lm; purple: typ. 225 lm; white: typ. 215 lm;	
Wood type	Alder	
Pastel colours	yes	
Surrounding temperature	0 125°C (permanently)	
LED lifetime	typ. 30,000 hours	
Automatic mode	interval lenght freely programmable (10 s to 4 h)	
Status memory	operation mode (single colour/automatic), colour, light intensity	

## Technical data power supply unit

Dimensions	75 x 34 x 43 mm	
Weight	ca. 160 g	
Input voltage	90 264 V <sub>AC</sub>	
Power consumption	max. 34 W	
Cable length	1,80 m	
Surrounding temperature	0 40°C	



www.collaxx.com



collaxx colour light units are protested by various national and international patents: DE 20 2009 011 688 U1 2010.01.14, DE 20 2009 011 690 U1 2010.02.11, DE 20 2009 011 691 U1 2010.01.14, DE 20 2009 011 694 U1 2010.01.14, DE 20 2009 011 698 U