

The little one with a miraculous price.



With the usual collaxx advantages:



Compatibility


There are no limits to your creativity:
You can arbitrarily combine all collaxx colour light units.



Invisible installation with bayonet connector

It is only a few steps to utter relaxation.

Ideal for retrofitting: Facile installation with only 2 screws.



Technical data colour light unit	FL50T	FL50F
Operation	change of colours by touching	see control options
Indirect illumination	limited possible	possible
Recommended cabin size	up to 1.3 x 1.3 m	
Dimensions	Ø 135 x 35 mm	
Weight	ca. 125 g	
Light intensity	red: typ. 73 lm; orange: typ. 92 lm; yellow: typ. 72 lm; green: typ. 49 lm; turquoise: typ. 52 lm; blue: typ. 14 lm; purple: typ. 72 lm; white: typ. 59 lm;	
Uniform light surface	yes	
Pastel colours	yes	
Surrounding temperature	0 125°C (permanently)	
LED lifetime	typ. 30,000 hours	
Automatic mode	interval lenght freely programmable (10 s to 4 h)	
Status memory	operation mode (single colour/automatic), colour, light intensity (only FL50F)	

Technical data power supply unit

Dimensions	64 x 30 x 45 mm	
Weight	ca. 90 g	
In <mark>pu</mark> t voltage	90 264 V _{AC}	
Power consumption	max. 16 W	
Cable length	1,37 m	
Surrounding temperature	0 40°C	



www.collaxx.com



collaxx colour light units are protected by various national and international patents: DE 20 2009 011 688 U1 2010.01.14, DE 20 2009 011 690 U1 2010.02.11, DE 20 2009 011 691 U1 2010.01.14, DE 20 2009 011 698 U